



**2X ULTRA COVER ENAMEL SPRAYS**

**DESCRIPTION AND USES**

Rust-Oleum® 2X Ultra Cover Enamel Sprays are designed to provide twice the coverage on wood, metal, plastic, wicker and more. These sprays cover surfaces with less spray passes, allowing projects to be completed faster and easier. 2X Ultra Cover Enamel Sprays feature an any angle spray that allows you to spray in any direction, even upside down. A comfort spray tip with a wider finger pad reduces fatigue caused by continuous spraying. Not for use on galvanised metal.

TIP: Some plastics made of polyethylene such as Little Tikes® children's products are manufactured in a way that may hinder maximum paint adhesion. Test paint in an inconspicuous area first.

**PRODUCTS**

SKU	Description
276262	Gloss Apple Red
276264	Gloss Berry Pink
276265	Gloss Colonial Red
276266	Gloss Deep Blue
276267	Gloss Grape
276268	Gloss Key Lime
276269	Gloss Kona Brown
276310	Gloss Meadow Green
276311	Gloss Real Orange
276312	Gloss Seaside
276313	Gloss Sun Yellow
276314	Gloss White
276315	Gloss Black
276316	Satin Blossom White
276317	Satin Canyon Black
276318	Satin Espresso
276319	Satin Heirloom White
276320	Satin Lagoon
276321	Satin Nutmeg
276322	Metallic Aluminium
276323	Flat Black
276324	Flat White
276345	Gloss Marigold
276347	Gloss Navy Blue
276348	Gloss Candy Pink
276349	Gloss Almond
276351	Gloss Dark Grey
276352	Satin Dark Walnut
276353	Satin Granite
276354	Satin Ivory Silk
286828	Satin Eden
286841	Gloss Ocean Mist
286843	Gloss Winter Grey
286844	Satin Poppy Red

**PRODUCT APPLICATION**

**PAINTING CONDITIONS**

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 10-32°C and humidity is below 65% to ensure proper drying. Do not apply to surfaces, when heated, exceed 93°C. Do not apply to galvanised steel. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

**SURFACE PREPARATION**

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with soap and water or other suitable cleaning method. Rinse thoroughly with fresh water and allow to thoroughly dry. All surfaces must be dry at time of application. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces.

**PRIMING**

Use of Rust-Oleum 2X primer provides excellent adhesion and hiding and is especially recommended for bare wood and metal.

**APPLICATION**

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 25-40 cm from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart to avoid drips and runs. Do not use near open flame.

**DRY & RECOAT TIMES**

Dry and recoat times are based on 21°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 20 minutes, to handle in 1 hour, and is fully dry in 24 hours. Apply a second coat or Clear coat within 1 hour or after 48 hours. Apply the clear coat in 2-3 light coats a few minutes apart. NOTE: On plastic, maximum paint adhesion and durability is achieved in 5-7 days.

**CLEAN-UP**

Wipe off tip before storing. Clean-up wet paint with mineral turps. Properly discard empty container. Do not burn or puncture the can even when empty.

**CLOGGING**

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral turps. Do not insert any object into the stem.

**TECHNICAL DATA****2X ULTRA COVER ENAMEL SPRAYS****PHYSICAL PROPERTIES**

		ENAMEL SPRAYS
<b>Resin Type</b>		Acrylic Modified Alkyd
<b>Pigment Type</b>		Varies with Colour
<b>Solvents</b>		Acetone, Ethyl Benzene, Xylene
<b>MIR</b>		Gloss & Flats 1.4 Max, Metallic Aluminum 1.9 Max
<b>Fill Weight</b>		340 grams
<b>Recommended Dry Film Thickness (DFT) per Coat</b>		25-50µ (1.0-2.0 mils)
<b>Practical Coverage at Recommended DFT (assumes 15% material loss)</b>		4.5 m <sup>2</sup> /can (48 sq.ft./can)
<b>Dry Times at 21-27°C (70-80°F) and 50% Relative Humidity</b>	<b>Touch</b>	20 minutes
	<b>Handle</b>	1 hour
	<b>Recoat</b>	Within 1 hour or after 24 hours
<b>Dry Heat Resistance</b>		93°C (200°F)
<b>Shelf Life</b>		5 years
<b>Flash Point</b>		-104°C (-156°F)
<b>Safety Information</b>		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Australia Pty, Ltd.  
Unit 12, 4 Southridge Street  
Eastern Creek, NSW 2766  
PH: 1 300 784 476  
www.rustoleum.com.au  
email: sales@rustoleum.com.au

HAYDN BRUSH CO. LTD.  
PO Box 4325  
Christchurch, New Zealand  
PH: 64 3 384 3210  
email: mail@haydn.co.nz

Form: GDH-507  
Rev.: 111714