

• TRUSTED QUALITY SINCE 1921 •



## TECHNICAL DATA

SPC-39

# SPECIALTY ULTRA COVER 2X CAMOUFLAGE SPRAYS

### DESCRIPTION AND USES

Rust-Oleum® Ultra Cover 2X Camouflage Sprays are flat, non-reflective spray paint designed for use on wood, metal, and other surfaces for the purpose of creating a camouflage pattern. The Ultra Cover 2X Camouflage Sprays are designed to spray at any angle, including an inverted position. Do not use on galvanized surfaces.

### APPEARANCE

Flat

### PRODUCTS

SKU	Description
279175	Deep Forest Green
279176	Army Green
279177	Khaki
279178	Earth Brown
279179	Black
279180	Sand

### PAINTING CONDITIONS

#### SURFACE PREPARATION

**ALL SURFACES:** Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Mold and mildew must be cleaned with a chlorinated cleaner or bleach solution. Rinse with fresh water and allow to thoroughly dry.

**STEEL:** Scrape and wire brush or power tool clean to remove loose rust, scale, and deteriorated coatings. Use 7569838 Red Primer for sound rusted or clean metal before application of a finish coat.

**PREVIOUSLY COATED:** Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy surfaces should be scarified by sanding to create a surface profile. Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. **LEAD IS TOXIC.** Contact the U.S.EPA/Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### PRODUCT APPLICATION (cont.)

#### APPLICATION

Apply only when air and surface temperatures are between 50-90°F (10-32°C) and the relative humidity is below 85% to ensure proper drying. Use outdoors or in areas with good ventilation. Avoid spraying in very windy or dusty conditions. Cover surrounding area to protect from overspray. Overspray can carry a significant distance. Shake can vigorously for one minute after the mixing ball begins to rattle. Shake often during use. Hold can 12-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Camouflage Sprays can also be sprayed in an inverted position. Keep the can the same distance from the surface. Keep the can in motion while spraying.

Apply a base coat of one color first. Then use leaves and twigs as stencils and lay them on the surface to make a random pattern. Then use three or more colors to paint stripes and patterns over the leaves and twigs. **Do not use near open flame.**

#### CLEAN-UP

Wipe off tip before storing. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

#### CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

• TRUSTED QUALITY SINCE 1921 •



## TECHNICAL DATA SPECIALTY ULTRA COVER 2X CAMOUFLAGE SPRAYS

### PHYSICAL PROPERTIES

ULTRA COVER 2X CAMOUFLAGE SPRAYS		
Resin Type	Acrylic Modified Alkyd	
Solvents	Acetone, Toluene, Xylene	
Fill Weight	12 oz.	
MIR	1.20 Max	
Practical Coverage at Recommended DFT (assumes 15% material loss)	Approximately 6-7 sq. ft./can (0.54-0.63 m <sup>2</sup> /can)	
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	20 minutes
	Handle	1 hour
	Recoat	Within 1 hour or after 24 hours
Dry Heat Resistance	200°F (93°C)	
Shelf Life	5 years	
Flash Point	-156°F (-104°C)	
Safety Information	For additional information, see MSDS	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, Illinois 60061  
An RPM Company

Phone: 877-385-8155  
[www.rustoleum.com](http://www.rustoleum.com)

Form: GDH-469  
Rev.: 091014